

ULTRA LOW TEMPERATURE FREEZER -86° C

MODELS	VOLUME (Lt)	INNER DIMENSIONS (mm)			OUTER DIMENSIONS (mm)			SHIPPING DIMENSION (mm)		
		W	D	H	W	D	H	W	D	H
B-ULT400	406 L	470	640	1350	750	920	1997	1060	1110	2250



CAPACITY GROSS/NET	406 L / 387 L
TEMPERATURE RANGE	-86° C / -40° C
AMBIENT TEMPERATURE	MAX.+ 25° C
POWER	230 V / 50 HZ / 6 Amp
ENERGY CONSUMPTION	12,2 Kw / 24 Hrs.
WEIGHT / SHIPPING WEIGHT	216 Kg / 340 Kg
MAX. SHELF LOAD	40 Kg Pr. Shelf
COOLING TECHNOLOGY	Cascade Cooling System
INTERFACE	Potential Free Remote Contact & RS485
DOCUMENTATION	IQ • OQ • Temperature mapping • Validation guidance

ENVIRONMENTAL EFFECTS

GWP	3 (R290) / 4 (R1150)
ODP	0 (R290) / 0 (R1150)



CONSTRUCTION

✓ Chamber Material Stainless Steel	✓ Magnetic Silicone Gasket	✓ Key Lock
✓ 4 pc pre made port hole	✓ Feet	✓ 4 Inner Door
✓ Heated Door Frame	✓ Vacuum release valve	✓ 3 Shelf
✓ Exterior Material Powder Coated Galvanized Steel	✓ Isolation Ecological Polyurethane Foam with V.I.P. Panels 120mm Thickness	

ALARMS

✓ Visual/Acoustic Alarm	✓ Open Door Alarm	✓ Contact Remote Alarm
✓ Power Failure Alarm	✓ Probe Failure Alarm	✓ Compressor Alarm
✓ Adjustable High / Low Temperature Alarm	✓ Track of Alarms & Events to be Noted Automatically	✓ Approx. 72 HRS. of Battery Backup for Alarms and Logging

DISPLAY

✓ Touch Screen	✓ Integrated Datalogger	✓ USB - Up & Download
✓ Memory For Over 15 Years Of Data	✓ Date & Time	✓ Password Protected
✓ Temperature Graph	✓ Intergrated Test Mode	✓ Ambient Temperature

DOCUMENTATION

✓ IQ	✓ OQ	✓ Temperature Mapping
✓ Pull Down	✓ Validation Guidance	

OPTIONAL RACKS & BOXES

RACKS	12 pcs	50MM BOXES	264
-------	--------	------------	-----

We reserve the right to change specifications without notice. Subject to confirmation, availability and errors.

We reserve the right to change specifications without notice. Subject to confirmation, availability and errors.